

POLYMORE duo 65-9,0

is a complete dissolving- and dosage equipment for liquid, concentrated polymer in emulsion- or dispersion form.

The equipment is complete, including mixing chamber with a built in agitator. The machine is delivered with a system for solvent water including valves, flow meter, a flow switch and a control cabinet with a built in pump for the concentrated polymer.

POLYMORE duo 65-9,0

is designed for a maximum capacity of **9 litres** concentrated polymer (product as supplied) per hour with a maximum flow of **4200 litres** water

Technical data:

Water flow - preparation water:	4 - 20 litres/ min
Water flow - dilution water:	5 - 50 litres/ min
Polymer flow - dosing pump:	8 - 150 ml/ min
Rated current:	max 4A
Voltage supply (acc. to IEC 60309-2):	230 VAC, 50 Hz, 1-fas
Control circuits (PELV):	24 VDC
Remote control:	Voltage free contact + 4 - 20 mA
Volume - mixing chamber:	22 litres (Ø265 x 400 mm)
Retention time:	5,5 - 1,0 min
Dimensions - W x D x H:	650 x 505 x 700 mm
Connection - water:	R1¼" - 32
Connection - polymer solution:	R1" - 25
Polymer dosing pump - type:	Peristaltic (tube) pump
Sound level:	< 60 dB(A)
Max. counter-pressure, polymer solution:	1 bar
Recommended running temperature:	+10 - +40 °C
Weight (empty chamber):	45 kg
Internal diameter of the pump tubing:	Ø 8,0 mm